

Portable Ultracapacitor Discharger



M3628PUD Series



Maintenance
Solutions



The M3628PUD ultracapacitor discharger is designed to deplete energy stored in ultracapacitor modules. It is capable of fully discharging the modules every 5 minutes. It includes a DC contactor for switching the resistor, a voltmeter for displaying the remaining voltage left on the module, 120VAC and 240VAC power cables, and 6 foot cables for connecting the module to the discharger.


Product Highlights

- Powered by standard 120VAC and 240VAC
- LED display to view remaining voltage
- Allows quick discharging of modules
- Tough impact and weather resistant case

Specifications

Voltage.....16 - 160 VDC
 Farads.....6 - 500 F
 Displays.....LED Voltage Indicator
 Operating Temp.....0°C to 40°C
 Storage Temp.....-20°C to +65°C
 Humidity.....Below 90% non-condensing
 Atmosphere.....Free of corrosive gas and conductive dust

Scan to view web page



Model Number Selection

Model Number	Capacitor Module			Resistor			Dimensions	Weight
	Voltage	Farads	Joules	Resistance	Peak Power	RMS Power		
M3628PUD-016-058	16 VDC	58 F	7.5 kJ	0.5 Ohms	500 W	100 W	6.0"H x 13.4"W x 11.7"D	9 lbs
M3628PUD-016-500	16 VDC	500 F	65 kJ	0.09 Ohms	2800 W	500 W	6.9"H x 16.5"W x 13.0"D	19 lbs
M3628PUD-048-166	48 VDC	166 F	190 kJ	0.16 Ohms	14.4 KW	1200 W	9.0"H x 22.0"W x 13.9"D	32 lbs
M3628PUD-160-006	160 VDC	6 F	75 kJ	5 Ohms	5000 W	400 W	6.9"H x 16.5"W x 13.0"D	16 lbs



www.bonitron.com



615-244-2825

info@bonitron.com

